



hpl WSZ

HAND SEALER

Compact and easy-to-operate hand sealer for professional closing of heat-sealable materials.

FLEXIBILITY AND EASY HANDLING: With this portable hand-held device you can seal heat seal-compatible plastic film and materials such as coated aluminium foil, coated paper or coated cellulose film easily and flexibly. The PTFE-coated models hpl WSZ TB prevent the materials from sticking on the sealing bars.

TECHNICAL DATA

	hpl WSZ 200	hpl WSZ 300	hpl WSZ 400
PTFE-uncoated	hpl WSZ 200	hpl WSZ 300	hpl WSZ 400
PTFE-coated	hpl WSZ 200 TB	hpl WSZ 300 TB	hpl WSZ 400 TB
Type of devices	Hand sealer		
Seal seam length	200 mm (7.9 in.)	300 mm (11.8 in.)	400 mm (15.7 in.)
Seal seam width	12 mm (0.5 in.)	12 mm (0.5 in.)	12 mm (0.5 in.)
Sealing temperature	50 – 250 °C (122 – 482 °F) infinitely adjustable		
Time of pre-heating	approx. 5 min.	approx. 5 min.	approx. 5 min.
Heating	via stamp above and below WING 500		
Power supply	Impulse device		
Power	350 VA	350 VA	350 VA
Mains connection	230 V, 50/60 Hz 115 V, 50/60 Hz	230 V, 50/60 Hz 115 V, 50/60 Hz	230 V, 50/60 Hz 115 V, 50/60 Hz
Weight	1,5 kg (2.2 lb.)	1,5 kg (2.2 lb.)	1,5 kg (2.2 lb.)

ACCESSORIES

Table clamp	WSZ-TK	WSZ-TK	WSZ-TK
-------------	--------	--------	--------

Subject to technical alterations 10/09 / 0 / WOLF / ST | 9.332.024
Printed in Germany

